

Technical Datasheet

tasker® C282 – 8x4,00 mm² Flexible PVC Speaker Cable



CATEGORY Flexible Speaker Cable
APPLICATIONS Professional Loudspeakers and premade cables

- A:** Black Soft PVC sheath. Outer Diam. Ø 16,60 (±0,20) mm.
B: Core Insulation with PVC Sheaths – Diam. Ø 4,20 (±0,20) mm.
Color Code:
1) Red 5) Yellow
2) Black 6) Grey
3) Blue 7) Brown
4) Green 8) Orange
C: O.F.C. red copper formation 128x0,20 mm.
Nom. Cross section 8x4,00 mm².

MARKING tasker® C282 – 8x4,00 mm² - O.F.C. - Loudspeaker Cable – Made In Italy
CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	5,74 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			