

MILAN S.r.l. a socio unico


Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® FSC12022 – 12x0,22 mm²

Firestop® Flexible Multi Conductor Cable



CATEGORY Multi Conductor Cable (See Electronics Catalogue)
APPLICATIONS Wiring and electronics

- A:** Black or Grey Soft **Flame Retardant PVC** sheath.
Outer cable Diam. Ø 6,80 (±0,20) mm.
- B:** Cores Insulation with Soft **Flame Retardant PVC**.
DIN 47100 Standards color: White, Brown, Green, Yellow, Grey, Pink, Blue, Red, Black, Violet, Grey/Pink, Red/Blue.
Diam. Ø 1,10 (±0,20) mm.
- C:** Stranded O.F.C. Red Copper formation 7x0,20 mm.
Nom. Cross section 12x0,22 mm².

MARKING **tasker® FSC 12022 12x0,22 mm² FLEX SHEATHED CABLE**
 Firestop® Made Italy

CUSTOM PRODUCTION This product may be custom produced also in **LSZH, PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			