

Technical Datasheet **tasker® T37 – 8x14 AWG** Flexible Speaker Cable

FirestoP®

✓RoHS₃



CATEGORY Flexible Speaker Cable (See news Brochure)
APPLICATIONS Professional Loudspeakers and premade cables

- A:** Flame Retardant black **PVC** sheath. Outer Diam. Ø 12,80 (±0,20) mm.
B: Core Insulation with PVC Sheaths – Diam. Ø 3,20 (±0,20) mm.
 Color Code:
 1) Red 5) Yellow
 2) Black 6) Grey
 3) Blue 7) Brown
 4) Green 8) Orange
C: O.F.C. red copper formation 43x0,25 mm.
 Nom. Cross section 8x14 AWG.

MARKING **tasker® T37 - 8x14 AWG - O.F.C. Loudspeaker Cable - FirestoP® - Made In Italy**
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	6,41 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. C / 04.10.23
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			