

Technical Datasheet

tasker® C279 – 4x4,00 mm² - Flexible Speaker Cable



A

B

C

CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables

- A:** Black Soft **PVC** Sheath. Available in different color.
Outer cable Diam. Ø 13,00 (±0,20) mm.
- B:** Core Insulation with PVC, colored: Red, Black, Light-Blue and Green.
Diam. Ø 4,20 (±0,20) mm.
- C:** O.F.C. red copper formation 128x0,20 mm.
Nom. Cross section 4x4,00 mm².

MARKING **tasker® C279 - 4x4,00 mm² – O.F.C. - Loudspeakers Cable – Made in Italy**
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	4,31 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			