



Technical Datasheet **tasker® T29 – 2x9 AWG** Flexible Loudspeaker Cable



CATEGORY Flexible Speaker Cable
APPLICATIONS Professional Loudspeakers and premade cables

- A:** Black **Flame Retardant PVC** Sheath.
 Outer cable Diam. Ø 14,40 (±0,20) mm.
- B:** Core Insulation with **PVC**, colored one Red and one Black.
 Diam. Ø 5,70 (±0,20) mm.
- C:** O.F.C. red copper formation 112x0,30 mm.
 Nom. Cross section 2x9 AWG.

MARKING **tasker® T29 2x9 AWG O.F.C. Loudspeaker Cable - FirestoP® - Made in Italy**
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	2,39 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 14.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			