

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet

# tasker® C112 – 2x0,35 mm<sup>2</sup> Balanced Microphone Cable



**CATEGORY** Balanced Microphone Cable (See Audio Catalogue)  
**APPLICATIONS** Pre Made Audio Cables and Microphones.

- A:** Black Soft PVC sheath. Outer Diam. Ø 6,30 (±0,20) mm.
- B:** Spiral Shielding O.F.C. tinned copper covering 100%
- C:** The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester based tape.
- D:** Transparent Cores Insulation with compact PE.  
Diam. 1,70 (±0,20) mm.
- E:** Stranded formation 11x0,20 mm, One conductor in O.F.C. red copper and one in O.F.C. tinned copper. Nom. cross section 2x0,35 mm<sup>2</sup>.

**MARKING** tasker® C 112 2X0,35 mm<sup>2</sup> O.F.C. FLEXIBLE MICROPHONE CABLE  
 FirestoP® CEI 20-22 II - MADE IN ITALY

**CUSTOM PRODUCTION** This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

### Cable Properties

<b>Conductor Resistance</b>	28 Ω/Km
<b>Capacity Core/Core</b>	55 pF/mt
<b>Capacity Core/Shield</b>	92 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-20/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>	<b>X</b>	Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			