

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® RNF3150 – 3x1,50 mm²

Heavy Duty Power Cable 450/750 V **Firestop®**



CATEGORY Heavy Duty Power Cable (See Electronics Catalogue)
APPLICATIONS Energy and electrical installation.

- A:** Black **Rubber** sheath, quality **EM2**. Chemical, Grease and Oils Resistant. Water Proof and good resistance to impact and heavy duty. Outer cable Diam. Ø 9,80 (±0,20) mm.
- B:** Core Insulation in **Neoprene rubber** quality **EI4**. Chemical, Grease and Oils Resistant. Water Proof and good resistance to impact and heavy duty. Diam. Ø 2,80 (±0,20) mm.
- C:** **O.F.C. red copper** formation with 0,25 mm elementary wires. Nom. Cross section 3x1,50 mm².

MARKING **tasker®** RNF3150 3G1.50 Extraflex Energy Cable 450/750 ICC IEMMEQU <HAR> H07RN-F 3G1,5

Cable Properties

Conductor Resistance	13,30 Ω/Km
Max Rated Voltage U₀/U	450/750V
Max Short Circuit Temp.	200°C/ 5 sec.
Mobile Bending Radius	4x Outer Diam.
Fix Bending Radius	3x Outer Diam.
Mobil Use Operative Temp.	-25/+60°C
Fix and protect Use Operative Temp.	-40/+60°C

USE	<input checked="" type="checkbox"/>	Indoor	Interno Edificio	INSTALLATION	<input checked="" type="checkbox"/>	Fixed	Fissa	INFORMATION	<input checked="" type="checkbox"/>	RoHS2 Compliant
Impiego	<input checked="" type="checkbox"/>	Outdoor Limited	Esterno Limitato	Posa	<input checked="" type="checkbox"/>	Flexible Limited	Flessibilità limitata	Informazioni	<input checked="" type="checkbox"/>	Ver. A / 15.07.16
	<input checked="" type="checkbox"/>	Outdoor Use	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
	<input checked="" type="checkbox"/>	Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			