

# Technical Datasheet

## tasker® C128 L.S.Z.H. – 2x0,35 mm<sup>2</sup>

### Low-Capacity Balanced Microphone Cable



**CATEGORY** Balanced Microphone Cable (See Audio Catalogue)  
**APPLICATIONS** Premade Cables and Microphones.

- A:** Soft **L.S.Z.H.** Sheath – Flame Retardant and Halogen Free.  
Outer cable Diam. Ø 6,30 (±0,20) mm.
- B:** Braided Shielding O.F.C. tinned copper covering 90%.
- C:** The cores are stranded in a pair with textile waste filler between conductors and wrapped with not woven polyester based tape.
- D:** Transparent Cores Insulation with compact PE. Diam. Ø 1,70 (±0,20) mm.
- E:** One conductor in O.F.C. red copper and one in O.F.C. tinned copper formation 11x0,20 mm. Nom. Cross section 2x0,35 mm<sup>2</sup>.

**MARKING** tasker® C128 L.S.Z.H. 2x0,35 mm<sup>2</sup> O.F.C. Low Capacitance Supreme Microphone Cable – Halogen Free - FirestoP® Made in Italy

**CUSTOM PRODUCTION** This product may be custom produced also in **PVC, PE, PUR**, with or without Metallic Armor.

#### Cable Properties

Conductor Resistance	58 Ω/Km
Capacity Core/Core	55 pF/m
Capacity Core/Shield	92 pF/m
Max Rated Voltage	49 V
Operative Temperature	-30/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 23.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			