

MILAN S.r.l. a socio Unico

Head Office - Export Department  
Viale Europa, 74  
20047 Cusago (MI) Italy  
Tel. +39 02 9039.4556 - 4158  
www.taskercables.com

Ufficio Commerciale e Distribuzione  
Viale Europa, 72 Strada F12  
20047 Cusago (MI) Italy  
Tel. +39 02 9039.0037 - 0059  
www.tasker.it

Capitale Sociale € 100.000,00 i.v.  
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154  
R.E.A. MI 975732 Reg. Imprese MI 178864-5179-14  
PEC: taskerpec@legalmail.it



## Technical Datasheet

# tasker® RG 59 eXtra 75 Ω Coaxial Cable



A	B	C	D
---	---	---	---

**CATEGORY**  
**APPLICATIONS**

Coaxial cable 75 Ω (See Video Catalogue)  
Standard definition video applications and cable assembly

- A:** Black Soft PVC black sheath.  
Outer cable diam. Ø 6,10 (±0,20) mm.
- B:** Shielding O.F.C. red copper Braid covering 80%.
- C:** Core Insulation with transparent PE. Dia. Ø 3,70 (±0,20) mm
- D:** Stiff Wire in CW, formation 1x0,58 mm.  
Nom. Cross section 1x0,26 mm<sup>2</sup>. (23 AWG).

**MARKING**  
**AVAILABLE ALSO**

**tasker®** RG 59 EXTRA 75Ω COAXIAL VIDEO CABLE  
RG59 BU, RG59 Flex, RG59 LSZH, RG59 Special, RG59 PUR,  
RG59 AR

**CUSTOM**  
**PRODUCTION**

This product may be custom produced also in PE, with or without  
Metallic Armor.

**Cable Properties**

<b>Conductor Resistance</b>	158 Ω/Km
<b>Capacity Core/Shield</b>	67 pF/m
<b>Velocity of Propagation</b>	66%
<b>Impedance</b>	75 Ω
<b>Max Rated Voltage</b>	2.000 V
<b>Operative Temperature</b>	-15/+70°C

**Attenuation dB/100 m.**

<b>50 MHz</b>	7,6
<b>100 MHz</b>	11,1
<b>200 MHz</b>	16,2
<b>400 MHz</b>	23,2
<b>800 MHz</b>	34,3
<b>1000 MHz</b>	38,7

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>	<b>X</b>	Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			