

Technical Datasheet

tasker® TSK302 – 2x1,50 mm²

Fire Detection Shielded Cable – PH120 – CPR - Cca Class



CATEGORY Fire Safety Cable CPR homologation (See audio catalogue)
APPLICATIONS Fire Detection systems.

- A:** Red **L.S.Z.H.** polymer grade M1. RAL 3000. Flame Retardant and halogen Free.
Resistant to direct fire for 120 minutes at max 850°C. RAL 3000.
Outer cable Ø 7,80 (±0,20) mm.
- B:** Shielding with metallic tape covering 100% + tinned copper drain Wire.
- C:** Core Insulation in **silicon rubber** grade G4, colored one Red and one Black.
Twisted together and grouped with PET tape. Diam. Ø 2,80 (±0,20) mm.
- D:** O.F.C. red copper formation 28x0,25 mm. Nom. Cross section 2x1,50 mm².

MARKING tasker® TSK302 – 2x1,50 mm² – Fire Detection Shielded Cable EN50200 (PH120) –
0987- CPR - 532 – 2024 – Cca – s1a – d1 – a1 - UNI 9795 – Uo/U 100/100 V - Uo =400V
– FirestoP® - Halogen Free - Made in Italy

NOTE The cables are suitable for application in the same conduit with circuits of electrical systems with rated voltage up to 400V to earth, typically 230/400V power systems.

Cable Properties

Conductor Resistance	13,30 Ω/Km
Max Rated Voltage	100 V
Max Pull Strength	15 kg/150N
Impedance	110 Ω
Min. Bending Radius	10xouterØ
Operative Temperature	-30/+70°C
Temperature Under Fire	850°C/120 min.

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. D / 31.08.22
	X	Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			