

Technical Datasheet **RoHS₃**

tasker® C103 TN – 2x0,22 mm² - Transparent Flat Cable



A

B

CATEGORY Flexible Audio Cable (See Audio Catalogue)
APPLICATIONS Speaker and Home Theatre installation

- A:** Transparent **PVC** Sheath. Outer Dimension 1,80x3,70 (±0,20) mm.
- B:** One conductor of O.F.C. tinned copper and one of O.F.C. Red Copper.
Stranded Formation with 0,20 mm.
Nominal cross section 2x0,22 mm².

MARKING tasker® C 103TN 2x0,22 mm² O.F.C. Speaker Cable
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.

Coductors Properties

Conductor Resistance	79,15 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 16.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			