

Technical Datasheet

tasker® C268 – 2x1,50 + 2x2,50 mm²

Flexible PVC Speaker Cable



CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional loudspeakers and premade cables

- A:** Soft **PVC** Sheath. - available in different color.
Outer cable Diam. Ø 10,00 (±0,20) mm.
- B:** Core Insulation with PVC Sheath.
Cores section 2x1,50 mm² have diam. Ø 3,00 (±0,20) mm.
and are colored one Red and one Black.
Cores section 2x2,50 mm² have diam. Ø 3,50 (±0,20) mm.
and are colored one Blue and one Green.
- C:** All conductors are made of O.F.C. red copper.
Cores section 2x1,50 mm² have a stranded formation 48x0,20 mm.
Cores section 2x2,50 mm² have a stranded formation 80x0,20 mm.

MARKING **tasker® C268 - 2x1,50+2x2,50 mm² – O.F.C. - Loudspeakers Cable**
– Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**,
with or without Metallic Armor.

Cable Properties

1,50 mm² Conductor Resistance	12,50 Ω/Km
2,50 mm² Conductor Resistance	6,41 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			