



MILAN S.r.l. a socio unico

Head Office – Export department:
Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it



Technical Datasheet

tasker® TSK902 – 2x2x0,25mm²



Fix Installation Digital Audio Multipair Cable CPR Cca Class



CATEGORY Digital Multipair Audio Cable (See News brochure)
APPLICATIONS Audio Mixers and Benches

- A:** Black **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free. Outer cable Ø: 10,20 (±0,20) mm
- B:** The single pairs are isolated with black **L.S.Z.H.**, numbered from one to the number of elements. Diam. Ø 3,80 (±0,20) mm.
- C:** The single pair are shielded with aluminum tape covering 100% + tinned copper Drain Wire.
- D:** The single cores are insulated with **foam skin PE**, colored one blue and one red. Diam. Ø 1,50 (±0,20) mm.
- E:** O.F.C. tinned copper formation 1x0,57 mm. Nom. Cross section 2x2x0,25 mm².

MARKING **tasker®** TSK902 CPR Cca - 2x2x0,25 mm² - Digital Audio Multipair cable AES/EBU 110Ω – CPR – Cca – s1–d1-a3 – Firestop® - Halogen Free – Made in Italy

Cable Properties

Conductor Resistance	75 Ω/Km	Impedance	110 Ω
Capacity Core/Core	45 pF/m	Max Rated Voltage	49 V
Capacity Core/Shield	100 pF/m	Operative Temperature	-15/+80°C

USE	<input checked="" type="checkbox"/>	Indoor	Interno Edificio	INSTALLATION	<input checked="" type="checkbox"/>	Fixed	Fissa	INFORMATION	<input checked="" type="checkbox"/>	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	<input checked="" type="checkbox"/>	Restricted Mobile	Mobile Limitata	Informazioni	<input checked="" type="checkbox"/>	Ver. A / 19.01.24
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			