

Technical Datasheet **RoHS₃** **FirestoP®**

tasker® TSK1117 - 2x4,00 mm² - Shielded Speaker Cable



A	B	C	D
---	---	---	---

CATEGORY APPLICATIONS

Special production shielded speaker cable
Professional loudspeakers and premade cables

- A:** Black Soft Flame Retardant PVC.
Outer cable Diam. Ø 11,00 (±0,20) mm.
- B:** Shielding in O.F.C. red copper braid, covering 85%.
- C:** The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester based tape.
Core Insulation with a compact PE, colored one Red and one Black
Diam. Ø 4,20 (±0,20) mm.
- D:** O.F.C. red copper formation 128x0,20 mm.
Nom. Cross section 2x4,00 mm².

MARKING

tasker® TSK1117 2x4,00 mm² – O.F.C. Shielded Speaker Cable
FirestoP® - Made in Italy

CUSTOM PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	4,31 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS3 Compliant
Informazioni	X	Ver. B / 26.05.19