

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C159 – 12x0,25 mm²

Flexible Multi Conductor Cable



NOTE
CATEGORY
APPLICATIONS

The picture does not represent the real number of conductors.
 Multi Conductor Cable (See Electronics Catalogue)
 wiring and electronics

- A:** Black Soft **PVC** Sheath.
Outer Diam. Ø 7,00 (±0,10) mm.
- B:** Cores Insulation with Soft **PVC** sheaths.
DIN 47100 Standards – White, Brown, Green, Yellow, Grey, Pink, Blue, Red, Black, Violet, Grey/Pink, Red/Blue.
Diam. Ø 1,40 (±0,20) mm.
- C:** Stranded O.F.C. Red Copper formation 8x0,20 mm.
Nom. Cross section 12x0,25 mm².

MARKING
CUSTOM
PRODUCTION

tasker® C 159 SHEATHED CABLE ITALY
 This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,** or Metallic Armored.

Cable Properties

Conductor Resistance	75,85 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			