

Technical Datasheet

tasker® C700 S.-F.T.P. Special LAN Cable



A	B	C	D	E	F
---	---	---	---	---	---

CATEGORY Twisted Pair LAN Cable (See Data Network Catalogue)
APPLICATIONS High Frequency Transmission Data

- A:** Soft Night Blue **PVC** sheath.
Outer cable diam. Ø: 7,00 (±0,10) mm.
- B:** First Shielding with a Braid of O.F.C. tinned copper covering 70%
+ tinned copper Drain Wire.
- C:** Second shielding with Aluminum tape, covering 100%.
- D:** The four pairs are stranded together with polyester-based tape.
- E:** Insulation with **PE**, diam. Ø 0,90 (±0,10) mm.
Core colors: White/Blu, White/Orange, White/Green, White/Brown,
White/Grey,
- F:** Stranded formation of 7x0,15 mm in O.F.C. Red Copper.
Nom. Cross section 5x2x0,14 mm².

MARKING **tasker®** C700 5x2x0,14 mm² Flex Data Twisted Pair Cable Made in Italy
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	138 Ω/Km
Impedance	100 Ω
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			