

Technical Datasheet

tasker® C708 L.S.Z.H. - U.T.P. CCA Cat. 5e Cable



CATEGORY Data Transmission Cable (See Data Network Catalogue)

APPLICATIONS LAN cabling and patch cord over Cat. cables

A: Black Soft **L.S.Z.H.** Sheath. Flame Retardant e Halogen Free.
Outdoor Limited. Outer Cable Diam. Ø 5,00 (±0,20) mm.

B: The four pairs are stranded together with polyester based tape.

C: Insulation with PE. Diam. Ø 0,90 (±0,20) mm.

RJ45 plug connector compatible.

Core colors: White – Blue/Blue White-Orange/ Orange,
White-Green/Green, White-Brown/Brown.

D: Stranded formation of 7x0,16 mm in CCA.
Nom. Cross section 4x2x0,14 mm².

MARKING

tasker® C708 L.S.Z.H. -U.T.P. cat. 5e 4Px14 mm² CCA Stranded
ISO 1801 100 MHz – FirestoP® - Halogen Free

CUSTOM PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
with or without Metallic Armor.

Cable Properties

Conductor Resistance	138 Ω/Km
Impedance	100 Ω
Max Rated Voltage	49 V
Operative Temperature	-30/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			