

Technical Datasheet

tasker® TSK71 – 2x0,50 mm² ✔ RoHS₃

Siliconic Flat Audio Divisible Cable for High Temperature



CATEGORY Flat Divisible Audio Cable
APPLICATIONS Medical, water park, beauty center, harsh environment and temperature

A: Extra Soft White Silicon Rubber sheath.
 Outer cable dimension 2,10x4,20 (±0,20) mm.

B: Both conductors in O.F.C. Tinned Copper.
 Stranded formation 16x0,20 mm.
 Nominal cross section 2x0,50 mm².

MARKING **tasker®** TSK71 - 2x0,50 mm² - O.F.C. – Siliconic Audio Cable - Temp.
 Range -60/+180°C – Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PVC** or **PUR**.

Coductors Properties

Conductor Resistance	40,10 Ω/Km
Operating Voltage	300V
Min. Bending Radius	4xouter Ø
Operative Temperature	-60/+180°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 14.04.26
	X	Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			