

Technical Datasheet

tasker® C100 – 2x1,50 mm²

Flat Divisible Audio Cable



A

B

CATEGORY Flexible Audio Cable (See Audio Catalogue)
APPLICATIONS Speaker and Home Theatre installation

A: Soft **PVC** Sheath, available in different colors.
Outer cable dimension 3,40 x 6,50 (±0,20) mm.

B: One conductor made of O.F.C. tinned copper and one of O.F.C. Red Copper. Formation with 0,20 mm wires.
Nominal cross section 2x1,50 mm².

MARKING Cable not Marked
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.

Coductors Properties

Conductor Resistance	12,50 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			