

MILAN S.r.l. a socio Unico

Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione
Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
R.E.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Technical Datasheet

tasker® RGB 75 L.S.Z.H. – 1x0,08 mm²

Special Coaxial Video cable 75 Ω



A	B	C	D
---	---	---	---

CATEGORY Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS standard video applications and mini coax assembly

- A:** Black Soft **L.S.Z.H. polymer**, Flame Retardant and with zero emission of halogen gasses. Outer cable Diam. Ø 2,80 (±0,10) mm.
- B:** Shielding in O.F.C. Silver Plated copper Braid covering 95%.
- C:** Core Insulation with transparent compact PE – Diam. Ø 1,50 (±0,10) mm
- D:** Stranded formation in O.F.C. red copper 9x0,10 mm.
Nom. Cross section 1x0,08 mm² (28 AWG).

MARKING **tasker®** RGB75 L.S.Z.H. – 75 OHM – MINI COAX VIDEO CABLE - FirestoP® - Halogen Free – Made Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H. polymer, PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	203 Ω/Km
Capacity Core/Shield	67 pF/m
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	30 V
Operative Temperature	-30/+70°C

Attenuation dB/100 m.

5 MHz	5,40	400 MHz	59,20
10 MHz	8,20	500 MHz	67,50
50 MHz	19,20	600 MHz	72,60
100 MHz	27,90	800 MHz	85,30
200 MHz	40,70	1000 MHz	101,00

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 29.05.19
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			