

## Technical Datasheet

### **tasker® C265 – 2x1,00 mm<sup>2</sup>**

### Flexible Double Density Sheath Speaker Cable



#### CATEGORY APPLICATION

Flexible Speaker Cable (See Audio Catalogue)  
Professional Loudspeakers and premade cables

- A:** First Soft **PVC** sheath, available in different color.  
Outer cable Diam. Ø 7,20 (±0,20) mm.
- B:** Second Soft **PVC** Sheath with different density.
- C:** Core Insulation in **PVC**, colored one Red and one Black.  
Diam. Ø 2,60 (±0,20) mm.
- D:** O.F.C. red copper formation 32x0,20 mm.  
Nom. Cross section 2x1,00 mm<sup>2</sup>.

#### MARKING

**tasker® C265 - 2x1,00 mm<sup>2</sup> – O.F.C. - Loudspeaker Cable**  
– Made In Italy

#### CUSTOM PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

#### Cable Properties

<b>Conductor Resistance</b>	18,80 Ω/Km
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			