

Technical Datasheet

tasker® TSK1118 - 2x6,00 mm² - Shielded Speaker Cable



CATEGORY Special production shielded speaker cable
APPLICATIONS Professional loudspeakers and premade cables

- A:** Black Soft Flame Retardant PVC.
Outer cable Diam. Ø 13,20 (±0,20) mm.
- B:** Shielding in O.F.C. red copper braid, covering 85%.
- C:** The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester based tape.
Core Insulation with a compact PE, colored one Red and one Black
Diam. Ø 5,00 (±0,20) mm.
- D:** O.F.C. red copper formation 122x0,25 mm.
Nom. Cross section 2x6,00 mm².

MARKING tasker® TSK1118 2x6,00 mm² – O.F.C. Shielded Speaker Cable
FirestoP® - Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	2,75 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 26.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			