

Technical Datasheet

tasker® TSK800 AES/EBU 110 Ohm Digital Audio Cable DMX



CATEGORY Digital Audio Cable (See Audio Catalogue)
APPLICATIONS Digital Audio premade cables and installations.

- A:** Black PVC Sheath.
Outer cable Diam. Ø 3,40 (±0,20) mm.
- B:** Shielding with aluminum tape covering 100%
+ tinned copper Drain Wire.
- C:** The pairs are wrapped with polyester tape.
- D:** The single cores are insulated with PEE, colored one white and one red.
Diam. Ø 1,20 (±0,20) mm.
- E:** O.F.C. tinned copper formation 18x0,10 mm.
Nom. Cross section 1x2x0,14 mm².

MARKING tasker® TSK800 1x2x0,14 mm² Extra Flex Digital Audio Pair Cable - Made in Italy
CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	138 Ω/Km
Capacity Core/Core	50 pF/m
Capacity Core/Shield	100 pF/m
Impedance	110 Ω
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 24.05.19
		Outdoor	Esterno			Mobile Drag Chain	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Torsione	Mobile in Torsione			