

Technical Datasheet

tasker® TSK 1038 L.S.Z.H. -2x0,35 mm²

DMX Digital Audio 110 Ohm Cable AES/EBU



A

B

C

D

E

CATEGORY Digital Audio Cable (See Audio Catalogue)

APPLICATIONS Digital Audio Applications and DMX Light

- A:** Black L.S.Z.H. sheath. Flame Retardant and Halogen Free.
Outer Diam. Ø 6,30 (±0,20) mm.
- B:** Shielding O.F.C. tinned copper Braid covering 85% + O.F.C. tinned copper Drain Wire.
- C:** Waste filler between conductors and total taping in not woven polyester.
- D:** Core Insulation with PPE, colored one Red and one Blue.
Core Diam. Ø 1,60 (±0,20) mm.
- E:** O.F.C. tinned copper formation 11x0,20 mm.
Nom. Cross section 2x0,35 mm².

MARKING

tasker® TSK 1038 L.S.Z.H. 2x0,35 mm² - O.F.C. Extra Flex Digital 110 Ω
DMX Audio Cable – Halogen Free - FirestoP® - Made In Italy

CUSTOM PRODUCTION

This product may be custom produced also in PVC, PE, PUR,
or Metallic Armored.

Cable Properties

Conductor Resistance	58,00 Ω/Km
Capacity Core/Core	55 pF/m
Capacity Core/Shield	62 pF/m
Impedance	110 Ω
Max Rated Voltage	49 V
Operative Temperature	-30/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			