

Technical Datasheet

tasker® T22 – 2x14 AWG - Flexible Loudspeaker Cable



CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Loudspeakers and Electronics.

- A:** Black Soft **Flame Retardant PVC** Sheath.
Outer cable Diam. Ø 8,20 (±0,20) mm.
- B:** Core Insulation with **PVC**, colored one Red and one Black.
Diam. Ø 3,10 (±0,20) mm.
- C:** O.F.C. red copper formation 43x0,25 mm.
Nom. Cross section 2x14 AWG.

MARKING **tasker®** T22 2x14AWG O.F.C. Loudspeaker Cable - FirestoP® - Made In Italy
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**,
PRODUCTION **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	8,80 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			