

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C196 – 2x0,50 mm² Balanced Microphone Cable



A	B	C	D	E
---	---	---	---	---

CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Premade Audio Cables and Microphones.

- A:** Soft transparent **PVC** Sheath.
Outer Diam. Ø 7,00 (±0,10) mm.
- B:** Braided Shielding O.F.C. tinned copper covering 95%.
- C:** Second PVC sheath between cores and shielding.
- D:** Transparent Cores Insulation with compact PE.
Diam. Ø 2,10 (±0,10) mm.
- E:** One conductor in O.F.C. red copper and one in O.F.C. tinned copper
formation 16x0,20 mm – Nom. cross section 2x0,50 mm².

MARKING **tasker®** C196 2x0,50 - 20 AWG O.F.C. Low Capacitance Supreme
Microphone Cable Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**,
with or without Metallic Armor.

Cable Properties

Conductor Resistance	38,00 Ω/Km
Capacity Core/Core	56 pF/m
Capacity Core/Shield	95 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated