

Technical Datasheet

tasker® T21 – 2x16 AWG

Flexible Loudspeaker Cable

FirestoP®

RoHS₃



A

B

C

CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables

- A:** Black Soft **Flame Retardant PVC** Sheath.
Outer cable Diam. Ø 7,40 (±0,20) mm.
- B:** Core Insulation with **Flame Retardant PVC** Sheath,
colored one Red and one Black.
Diam. Ø 2,20 (±0,20) mm.
- C:** O.F.C. red copper formation 28x0,25 mm.
Nom. Cross section 2x16 AWG.

MARKING **tasker® T21 2x16 AWG O.F.C. Loudspeaker Cable - FirestoP® - Made In Italy**
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,**
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	12,50 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			