

Technical Datasheet

tasker® C404 – 4x2x0,22 mm²

Single Shielded Multipair Audio Cable



A	B	C	D	E
---	---	---	---	---

CATEGORY

APPLICATIONS

Multipair Audio Cable (See Audio Catalogue)

Audio Mixers, Benches and Audio Balanced multi sockets.

- A:** Soft Black **PVC** Sheath. Outer cable Diam. Ø: 10,20 (±0,20) mm.
- B:** The single pair are isolated with black **PVC**, numbered from one to the number of elements and wrapped together with polyester base tape.
Diam. Ø 3,00 (±0,20) mm.
- C:** The single pair are shielded with spiral in O.F.C. red copper, covering 100% + tinned copper Drain Wire.
- D:** The single cores are insulated with **Solid PE**, colored one Yellow and one Transparent, and wrapped with not weaved polyester base tape.
Diam. Ø 1,00 (±0,20) mm.
- E:** O.F.C. red copper formation 28x0,10 mm.
Nom. Cross section 4x2x0,22 mm².

MARKING

tasker® 4x2x0,22mm² Professional Multipair Cable for Audio Mixer –
Made in Italy

CUSTOM

PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	75 pF/m
Capacity Core/Shield	160 pF/m
Velocity of Propagation	66%
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			