

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com


**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



# Technical Datasheet

## **tasker® C448 – 48x2x0,22 mm<sup>2</sup>**

### Single Shielded Multipair Audio Cable



**NOTE**  
**CATEGORY**  
**APPLICATIONS**

The picture don't represent the real number of conductors  
 Multipair Audio Cable (See Audio Catalogue)  
 Audio Mixers, Benches and Audio Balanced multi sockets.

- A:** Soft Black **PVC** Sheath.  
Outer cable Diam. Ø: 27,00 (±0,10) mm.
- B:** The single pair are isolated with black **PVC**, numbered from one to the number of elements and wrapped together with polyester base tape.  
Diam. Ø 3,00 (±0,10) mm.
- C:** The single pair are shielded with spiral in O.F.C. red copper, covering 100% + tinned copper Drain Wire.
- D:** The single cores are insulated with **Solid PE**, colored one Yellow and one Transparent, and wrapped with not weaved polyester base tape.  
Diam. Ø 1,00 (±0,10) mm.
- E:** O.F.C. red copper formation 28x0,10 mm.  
Nom. Cross section 48x2x0,22 mm<sup>2</sup>.



MILAN S.r.l. a socio unico

**Head Office – Export department:**

Viale Europa, 74  
20090 Cusago (MI) Italy  
T. +39 02 9039.4556-4158  
F. +39 02 9039.4551  
www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**

Viale Europa 72 Strada F12  
20090 Cusago (MI) Italy  
T. +39 02 9039.0037-0059  
F. +39 02 9039.0049  
www.tasker.it

**MARKING**

**tasker®** C448 48x2x0,22mm<sup>2</sup> Professional Multipair Cable for Audio Mixer –  
Made in Italy

**CUSTOM  
PRODUCTION**

This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**,  
with or without Metallic Armor.

**Cable Properties**

<b>Conductor Resistance</b>	79,15 Ω/Km
<b>Capacity Core/Core</b>	75 pF/mt
<b>Capacity Core/Shield</b>	160 pF/mt
<b>Velocity of Propagation</b>	66%
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			