

Technical Datasheet

tasker® C300 – 1x0,22 mm²

Guitar Cable with Carbon Screen



CATEGORY Instrumental Cable (See Audio Catalogue)
APPLICATIONS Premade cables for instrumental cable like Guitar, Bass and Keyboards

- A:** Black Soft PVC Sheath. Outer Diam. Ø 6,00 (±0,10) mm.
- B:** First shielding with O.F.C. red copper Spiral covering 100%.
- C:** Conductive carbon screen covering.
- D:** Transparent PPE insulation. Diam. Ø 1,50 (±0,10) mm.
- E:** O.F.C. stranded tinned copper formation 7x0,20 mm.
Nom. Cross section 1x0,22 mm².

MARKING tasker® C300 1X0.22 - 24 AWG - O.F.C. Professional Noiseless Guitar Cable
 Low Capacity - Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,
 with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/km
Capacity Core/Shield	88 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			