

Technical Datasheet

tasker® C200 – 2x0,08 mm² Special Audio/Video Cable



CATEGORY Special Audio/Video Cable (See video Catalogue)
APPLICATIONS S-VHS and Mini DIN4 connectors.

- A:** Black PVC Sheath. Outer cable Diam. Ø 4,60 (±0,20) mm.
- B:** Insulation with PVC, colored one Red and one White.
Diam. Ø: 2,00 (±0,20) mm.
- C:** Each conductor is Shielded with O.F.C. tinned copper spiral covering 100%.
- D:** Conductors insulation in PVC, colored one Yellow and one Grey.
Diam. 1,00 (±0,20) mm.
- E:** O.F.C. tinned copper formation 12x0,10 mm.
Nom. Cross section 2x0,08 mm². (28 AWG)

MARKING tasker® C200 - 2x0,08 mm² O.F.C. S-VHS Video Cable
CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, or Metallic Armored.

Cable Properties

Conductor Resistance	203 Ω/Km
Capacity Core/Core	65 pF/m
Capacity Core/Shield	230 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	<input checked="" type="checkbox"/>	Indoor	Interno Edificio	INSTALLATION	<input checked="" type="checkbox"/>	Fixed	Fissa	INFORMATION	<input checked="" type="checkbox"/>	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	<input checked="" type="checkbox"/>	Restricted Mobile	Mobile Limitata	Informazioni	<input checked="" type="checkbox"/>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			