

MILAN S.r.l. a socio Unico

Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione
Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
R.E.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Technical Datasheet

tasker® C208 – 2x0,25 mm²



Low Capacity Balanced Microphone Cable



CATEGORY Balanced Microphone Cable (See Audio Catalogue)

APPLICATIONS Pre Made Audio Cables and Microphones.

- A:** PVC Sheath. Available in different color.
Outer cable Diam. Ø 6,20 (±0,20) mm.
- B:** Shielding O.F.C. red copper braid covering 95%.
- C:** The cores are stranded in a pair with textile waste filler between conductors and wrapped with not woven polyester-based tape.
- D:** Core Insulation with a compact PE, colored one White and one Blue. Diam. Ø 1,60 (±0,20) mm.
- E:** O.F.C. red copper, formation 8x0,20 mm.
Nom. Cross section 2x0,25 mm².

MARKING tasker® C208 2x0,25 mm² - 23 AWG – Professional Noiseless Microphone – Low Capacity

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	75,85 Ω/Km
Capacity Core/Core	51 pF/m
Capacity Core/Shield	88 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 13.09.23
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			