

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet



tasker® FSC16022 – 16x0,22 mm² Flexible Multi Conductor Cable



A	B	C
---	---	---

NOTE

The picture do not represent the real number of conductors.

CATEGORY

Multi Conductor Cable (See Electronics Catalogue)

APPLICATIONS

Wiring and Electronics.

- A:** Soft **Flame Retardant PVC** sheath. Available in different colors.
Outer cable diam Ø 7,20 (±0,20) mm.
- B:** Cores Insulation with Soft **Flame Retardant PVC**.
DIN 47100 Standards: White, Brown, Green, Yellow, Grey, Pink, Blue, Red, Black, Violet, Grey/Pink, Red/Blue, White/Green, Brown/Green, White/Yellow and Yellow/Brown. Core Diam. Ø 1,10 (±0,20) mm.
- C:** Stranded O.F.C. Red Copper formation 7x0,20 mm.
Nom. Cross section 16x0,22 mm².

MARKING

tasker® FSC 16022 16x0,22 mm² FLEX SHEATHED CABLE Firestop® Made Italy

CUSTOM

This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

PRODUCTION

Cable Properties

Conductor Resistance	79,15 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			