

Technical Datasheet

tasker® C255 – 2x0,22 mm²

Balanced Microphone Cable



CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Premade Audio Cables and Microphones.

- A:** Black Soft **PVC** Sheath. Outer cable Diam. Ø 5,00 (±0,20) mm.
- B:** Braided Shielding O.F.C. red copper covering 60%.
- C:** The cores are stranded in a pair with textile waste filler between conductors and wrapped with not woven polyester based tape.
- D:** Cores Insulation with compact PE. Colored one white and one yellow.
Diam. Ø 1,20 (±0,20) mm.
- E:** Conductors in O.F.C. red copper with stranded formation 7x0,20 mm.
Nom. Cross section 2x0,22 mm².

MARKING **tasker® C255 2x0,22 mm² O.F.C. Shielded Audio Cable.**
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
PR ODUCTION or Metallic Armored.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	66 pF/m
Capacity Core/Shield	113 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			