

Technical Datasheet

tasker® TSK406 – 2x6,00 mm²

Fix Installation Speaker Cable - CPR Cca Class



CATEGORY Fix Installation Speaker Cable (See News brochure)
APPLICATIONS Professional Loudspeakers

- A:** Black **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free.
Outer cable Ø: 12,40 (±0,20) mm.
- B:** Core Insulation in L.S.Z.H., colored one Red and one Black. Diam. Ø: 5,00 (±0,20) mm.
- C:** O.F.C. red copper formation 84x0,30 mm.
Nom. Cross section 2x6,00 mm².

MARKING **tasker® TSK406 CPR Cca - 2x6,00 mm² - Loudspeaker Cable -CPR- Cca**
– s1–d1-a3 – Firestop® - Halogen Free – Made in Italy

NOTE The cables are suitable for application in the same conduit with circuits of electrical systems with rated voltage up to 400V to earth, typically 230/400V power systems.

Cable Properties

Conductor Resistance	2,75 Ω/Km
Max Rated Voltage	100 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 19.01.24
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			