

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Firestop® Technical Datasheet **Halogen Free**

tasker® TSK1038 CPR Cca – 2x0,35 mm²

DMX Digital Audio 110 Ohm Cable AES/EBU



A	B	C	D
---	---	---	---

CATEGORY Digital Audio Cable (See News brochure)

APPLICATIONS Digital Audio application and DMX light on Fix Installation

- A:** Black L.S.Z.H. Sheath UV resistant.
Outer cable Diam. Ø 6,20 (±0,20) mm.
- B:** Braided Shielding O.F.C. tinned copper covering 85%
+ Aluminum foil tape.
- C:** The cores are stranded in a pair with two Flame Retardant PVC filler.
Cores insulation in Foam PE, colored one red and one blue.
- D:** Diam. Ø 2,00 (±0,20) mm.
- E:** O.F.C. tinned copper stranded formation 7x0,25 mm.
Nom. Cross section 2x0,35 mm².

MARKING **tasker®** TSK1038 CPR Cca - 2x0,35 mm² – 110Ω DMX Audio Cable
 - 2479-CPR-E01666 – Cca – s1– d2–a3 – Firestop® - Halogen Free
 - Made in Italy

Cable Properties

Conductor Resistance	56,50 Ω/Km
Capacity Core/Core	46 pF/m
Capacity Core/Shield	92 pF/m
Impedance	110 Ω
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	<input checked="" type="checkbox"/>	Indoor	Interno Edificio	INSTALLATION	<input checked="" type="checkbox"/>	Fixed	Fissa	INFORMATION	<input checked="" type="checkbox"/>	RoHS2 Compliant
Impiego	<input checked="" type="checkbox"/>	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	<input checked="" type="checkbox"/>	Ver. B / 05.09.22
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			