

Technical Datasheet

tasker® C191 TS – 2x1,00 mm²

Extra Flex Transparent Flat Speaker Cable



A

B

CATEGORY Flexible Audio Cable (See Audio Catalogue)
APPLICATIONS Speaker and Home Theatre installation

- A:** Soft Transparent **PVC** sheath.
Outer cable dimension 2,80x5,60 (±0,20) mm.
- B:** One conductor made of O.F.C. tinned copper and one of O.F.C. Red Copper, both realized with elementary wires stranded in beams and stranded again to create cores.
Nominal cross section 2x1,00 mm², formation 18x7x0,10 mm.

MARKING **tasker® C191TS - 2x1.00 mm² – O.F.C. SPEAKER CABLE - MADE IN ITALY**
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.
PRODUCTION

Coductors Properties

Conductor Resistance	18,80 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			