

Technical Datasheet

tasker® C112 – 2x0,35 mm²

Balanced Microphone Cable



CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Pre Made Audio Cables and Microphones.

- A:** Black Soft PVC sheath. Outer Diam. Ø 6,30 (±0,20) mm.
B: Spiral Shielding O.F.C. tinned copper covering 100%
C: The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester based tape.
D: Transparent Cores Insulation with compact PE.
 Diam. 1,70 (±0,20) mm.
E: Stranded formation 11x0,20 mm, One conductor in O.F.C. red copper and one in O.F.C. tinned copper. Nom. cross section 2x0,35 mm².

MARKING **tasker® C112 – 2x0,35 mm² - O.F.C. FLEXIBLE MICROPHONE CABLE**
FirestoP® - MADE IN ITALY

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	28 Ω/Km
Capacity Core/Core	55 pF/m
Capacity Core/Shield	92 pF/m
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			