

Technical Datasheet

tasker® TSK402 CPR Cca – 2x1,50 mm² **Fix Installation Speaker Cable**



CATEGORY Fix Installation Speaker Cable (See News brochure)
APPLICATIONS Professional Loudspeakers

- A:** Black **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free.
Outer cable Ø: 7,20 (±0,20) mm.
- B:** Core Insulation in **L.S.Z.H.**, colored one Red and one Black.
Diam. Ø: 2,70 (±0,20) mm.
- C:** O.F.C. red copper formation 30x0,25 mm.
Nom. Cross section 2x1,50 mm².

MARKING **tasker® TSK402 CPR Cca - 2x1,50 mm² - Loudspeaker Cable - 0987-CPR-721**
– Cca – s1–d1–a3 – FirestoP® - Halogen Free – Made in Italy

NOTE The cables are suitable for application in the same conduit with circuits of electrical systems with rated voltage up to 400V to earth, typically 230/400V power systems.

Cable Properties

Conductor Resistance	13,30 Ω/Km
Max Rated Voltage	100 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 06.09.24
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			