

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet



tasker® C812 – 12x2x0,22 mm² Digital Audio Multipair Cable 110 Ohm AES/EBU



| | | | | | |
|---|---|---|---|---|---|
| A | B | C | D | E | F |
|---|---|---|---|---|---|

NOTE
CATEGORY
APPLICATIONS

The picture don't represent the real number of conductors
 Digital Multipair Audio Cable (See Audio Catalogue)
 Audio Mixers, Benches and Audio Balanced multi sockets.

- A:** Soft Black **Flame Retardant PVC** Sheath.
Outer cable Diam. Ø 19,30 (±0,10) mm.
- B:** The pairs are wrapped together with polyester base tape.
- C:** The single pair are isolated with black **Flame Retardant PVC**, numbered from one to the number of elements. Diam. Ø 4,00 (±0,10) mm.
- D:** The single pair are shielded with O.F.C. Red copper spiral covering 100% + tinned copper Drain Wire.
- E:** The single cores are insulated with **PPE**, colored one blue and one red.
Diam. Ø 1,50 (±0,10) mm.
- F:** O.F.C. tinned copper formation 28x0,10 mm.
Nom. Cross section 12x2x0,22mm².

MARKING

tasker® C812 12x2x0,22 mm² AES/EBU 110 OHM DIGITAL MULTIPAIR AUDIO CABLE - Firestop® - CEI 20-22 II - Made In Italy

MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione

Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it

**CUSTOM
PRODUCTION**

This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

| | |
|------------------------------|--------------------|
| Conductor Resistance | 79,15 Ω /Km |
| Capacity Core/Core | 50 pF/mt |
| Capacity Core/Shield | 95 pF/mt |
| Impedance | 110 Ω |
| Max Rated Voltage | 49 V |
| Operative Temperature | -20/+70°C |

| | | | | | | | | | | |
|----------------|----------|-----------------------|-------------------|---------------------|----------|----------------------|------------------|---------------------|----------|-------------------|
| USE | X | Indoor | Interno Edificio | INSTALLATION | X | Fixed | Fissa | INFORMATION | X | RoHS2 Compliant |
| Impiego | | Outdoor Limited | Esterno Limitato | Posa | X | Restricted Mobile | Mobile Limitata | Informazioni | X | Ver. A / 16.05.16 |
| | | Outdoor | Esterno | | | Mobile | Mobile | | | |
| | | Outdoor Direct Burial | Esterno Interrato | | | Mobile in Drag Chain | Mobile in Catena | | | |