



## Technical Datasheet

# tasker® TSK401 – 2x1,00 mm<sup>2</sup>

### Fix Installation Speaker Cable - CPR Cca Class



**CATEGORY** Fix Installation Speaker Cable (See News brochure)  
**APPLICATIONS** Professional Loudspeakers

- A:** Black **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free. Outer cable Ø: 7,10 (±0,20) mm.
- B:** Core Insulation in silicon rubber grade G4, colored one Red and one Black. Twisted together and grouped with PET tape. Diam. Ø: 2,40 (±0,20) mm.
- C:** O.F.C. red copper formation 32x0,19 mm. Nom. Cross section 2x1,00 mm<sup>2</sup>.

**MARKING** **tasker®** TSK401 2x1,00 mm<sup>2</sup> - O.F.C. Loudspeaker Cable - 0987-CPR-538 – 2022 –

**NOTE** Cca – s1a – d0 – a1 – Uo/U 100/100 V – FirestoP® - Halogen Free - Made in Italy  
 The cables are suitable for application in the same conduit with circuits of electrical systems with rated voltage up to 400V to earth, typically 230/400V power systems.

#### Cable Properties

<b>Conductor Resistance</b>	19,50 Ω/Km
<b>Max Rated Voltage</b>	100 V
<b>Operative Temperature</b>	-30/+70°C

<b>USE</b>	X	Indoor	Interno Edificio	<b>INSTALLATION</b>	X	Fixed	Fissa	<b>INFORMATION</b>	X	RoHS2 Compliant
<b>Impiego</b>	X	Outdoor Limited	Esterno Limitato	<b>Posa</b>		Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	X	Ver. A / 29.05.20
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			