

MILAN S.r.l. a socio Unico

Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione
Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
RE.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it



Technical Datasheet

tasker® C226 – 1x0,08 (75Ω) +2x0,50 mm²

Special Video Cable

Firestop®



CATEGORY Video Cable 75Ω (See video Catalogue)
APPLICATIONS Video installations, Security and Video Cameras.

A: Black Soft **Flame Retardant PVC** Sheath.
Outer cable Diam. Ø 6,60 (± 0,20) mm.

75 Ω Video Coax:

B: Inner Sheath in **Flame Retardant PVC**.
Diam. Ø 2,80 (± 0,20) mm.
C: Spiral Shielding in O.F.C. tinned Copper covering 100%.
D: Dielectric in white **PEE**. Diam. Ø 1,50 (± 0,20) mm.
E: Stranded O.F.C. red copper formation 10x0,10 mm.
Nom. Cross section 1x0,08 mm². (28 AWG)

Insulated cores:

F: Inner Sheaths in **Flame Retardant PVC**.
Both Colored Black. Diam. Ø 1,90 (± 0,20) mm.
G: Stranded formations 16x0,20 mm, one conductor in O.F.C. tinned copper and one in red copper. Nom. Cross section 2x0,50 mm². (20 AWG)

MARKING **tasker®** C226 1x0,75Ω + 2x0,22 mm² - O.F.C. Special Video Cable
Firestop® - Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

MILAN S.r.l. a socio Unico

Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione
Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
R.E.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Coaxial Properties

Insulated Conductors Resistance	38,00 Ω/Km
Coax Conductor Resistance	203 Ω/Km
Coax Capacity Core/Shield	67 pF/m
Coax Velocity of Propagation	66%
Coax Impedance	75 Ω
Max Rated Voltage	49V
Operative Temperature	-20/+70°C

Attenuation dB/100 m.

50 MHz	19,50
100 MHz	28,50
200 MHz	41,70
400 MHz	60,20
800 MHz	87,30
1000 MHz	103,00

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 26.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			