

MILAN S.r.l. a socio Unico

Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione

Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.

Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
R.E.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Technical Datasheet **RoHS₃**

tasker® RG 59 BU 75 Ω Coaxial Mil. C 17 F Standard Cable



A	B	C	D
---	---	---	---

CATEGORY APPLICATIONS

Coaxial cable 75 Ω (See Video Catalogue)
Standard definition video applications and cable assembly

- A:** Black Soft **PVC** Sheath. Outer Diam. Ø 6,10 (±0,20) mm.
B: Shielding O.F.C. red copper Braid covering 95%.
C: Core Insulation with transparent compact PE. Diam. Ø 3,70 (±0,20) mm
D: Stiff Wire formation in CW 1x0,58 mm (20 AWG).
 Nom. Cross section 1x0,26 mm²

MARKING AVAILABLE ALSO

tasker® RG59 75 Ohm Mil. - C17/F Coaxial Video Cable Italy
RG59 BU, RG59 Flex, RG59 LSZH, RG59 eXtra, RG59 PUR,
RG59 AR

CUSTOM PRODUCTION

This product may be custom produced also in **PE**, with or without
Metallic Armor.

Cable Properties

Conductor Resistance	158 Ω/Km
Capacity Core/Shield	67 pF/m
Velocity of Propagation	66%
Impedance	75 Ω
Nom. Delay	5,07 ns/m
Max Rated Voltage	2.000 V
Operative Temperature	-15/+70°C

Attenuation dB/100 m.

100 MHz	10,7
200 MHz	15,7
400 MHz	22,7
500 MHz	25,7
600 MHz	28,7
800 MHz	33,6
1000 MHz	38,0

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 16.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			