

MILAN S.r.l. a socio Unico

Head Office - Export Department  
Viale Europa, 74  
20047 Cusago (MI) Italy  
Tel. +39 02 9039.4556 - 4158  
www.taskercables.com

Ufficio Commerciale e Distribuzione  
Viale Europa, 72 Strada F12  
20047 Cusago (MI) Italy  
Tel. +39 02 9039.0037 - 0059  
www.tasker.it

Capitale Sociale € 100.000,00 i.v.  
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154  
R.E.A. MI 975732 Reg. Imprese MI 178864-5179-14  
PEC: taskerpec@legalmail.it

## Technical Datasheet

# tasker® C700 S.-F.T.P.

## Special 5 Pairs LAN Cable



**CATEGORY** Twisted Pair LAN Cable (See Data Network Catalogue)  
**APPLICATIONS** High Frequency Transmission Data

- A:** Soft Night Blue PVC sheath.  
Outer cable diam. Ø: 7,00 (±0,10) mm.
- B:** First Shielding with a Braid of O.F.C. tinned copper covering 70%  
+ tinned copper Drain Wire.
- C:** Second shielding with Aluminum tape, covering 100%.
- D:** The four pairs are stranded together with polyester-based tape.
- E:** Insulation with PE, diam. Ø 0,90 (±0,10) mm.  
Core colors: White/Blu, White/Orange, White/Green,  
White/Brown, White/Grey.
- F:** Stranded formation of 19x0,10 mm in O.F.C. Tinned Copper.  
Nom. Cross section 5x2x0,14 mm<sup>2</sup>.

**MARKING** tasker® C700 - 5x2x0,14 mm<sup>2</sup> - Flex Data Twisted Pair Cable - Made in Italy  
**CUSTOM** This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,  
**PRODUCTION** with or without Metallic Armor.

### Cable Properties

<b>Conductor Resistance</b>	138 Ω/Km
<b>Impedance</b>	100 Ω
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	X	Indoor	Interno Edificio	<b>INSTALLATION</b>	X	Fixed	Fissa	<b>INFORMATION</b>	X	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	X	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	X	Ver. B / 12.12.25
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			