

Technical Datasheet

tasker® TSK1140 – 1x0,05 mm²

Shielded Unipolar Miniature Cable



CATEGORY Miniature Cable (See Audio Catalogue)
APPLICATIONS Earphones, headphones and electronics.

- A:** Soft transparent PVC sheath.
Outer Cable diameter Ø 1,70 (±0,15) mm.
- B:** Shielding in tinned and enameled copper braid covering 100%.
- C:** Core Insulation with red PVC. Nom. diam. Ø 0,60 (±0,15) mm.
- D:** Enameled Red Copper + Nylon formation 28x0.05 mm.
Nom. Cross section 1x0,05 mm².

MARKING **tasker®** TSK1140 1x0,05 mm² O.F.C. + Nylon Micro Audio Cable
CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	174 Ω/Km
Capacity Core/Shield	305 pF/m.
Max Rated Voltage	30 V
Operative Temperature	-20/+60°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. C / 18.03.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			